

CHANGE-KIT-15

CFMOTO X450/X520/X550/X600/X850/X1000

ENGINE OIL CHANGE KIT INSTRUCTIONS

Engine oil change:

- Place the ATV on a level surface and secure it against rolling away.
 - Select Neutral, start the engine, let it warm up on idle for cca 5 minutes and turn the engine off.
 - Place a suitable container / pan that holds at least 3.5 liters under the engine.
 - Loosen the drain plug at the bottom of the engine. Do not drop the screw into the pan.
 - Carefully drain warm oil and allow it to drain completely. **WARNING: OIL CAN BE VERY HOT!**
 - Remove the oil filter. The oil filter is located under the plastic cover on the right side of the engine.
 - Allow the oil to drain from the engine and filter.
 - Wipe away any spilled oil.
 - Insert new oil filter into the engine.
 - Screw the oil filter cover back on. (Tightening torque is in user manual). Replace the plastic cover.
 - Screw the oil drain plug back into the engine.
 - Unscrew and remove the oil dip stick – the oil filling point.
 - Using a funnel, carefully pour about 2 liters (for CFMOTO X850/X1000) or 2.5 liters (for CFMOTO X450/X520/X550/X600) of 10W-40 oil into the engine. Avoid overfilling the funnel.
 - Put the dip stick on top of the threads (do not screw it in), pull the dip stick out and check the oil level.
 - If the oil level is low, top up the oil.
 - If the oil level reaches the upper mark on the dip stick, reinstall the dip stick.
 - In general, you should use about 2.5 liters (for CFMOTO X850/X1000) or 2.9 liters (for CFMOTO X450/X520/X550/X600) of oil when changing.
 - Clean spilled oil, start the engine and check for oil leaks.
 - After cca. 1 minute stop the engine, wait for about 10 seconds, unscrew the oil dip stick again and wipe it with a clean rag. Put the dip stick on top of the threads (do not screw it in), pull the dip stick out and check the oil level.
 - The oil level should be between the upper and lower marks.
 - If not, add the oil to the correct level by repeating the steps above.
 - Once the oil level is correct, screw the dip stick back into the engine and wipe off any oil residues.
- Congratulations: you have successfully replaced your oil and oil filter!
- Dispose of the used oil ecologically - take your used oil and oil filter in for recycling.

CHANGE-KIT-15 includes:

- **3x 1L MAXIMA ATV PREMIUM 10W40 4T Oil**, Part: 33901
- **1x OIL FILTER ProFilter MAXIMA**, Part: PF-152
- **Instruction sheet**



OFFICIAL DISTRIBUTOR:

ASP Group Distributing, Staropltzenecka 290, 326 00, Letkov, CZ, tel: +420 378 21 21 21, info@aspgroup.cz, www.aspgroup.eu