



## CHANGE-KIT-02

### ENGINE OIL AND OIL FILTER REPLACEMENT INSTRUCTIONS - TGB 1000

- Place the ATV on a level surface.
- Start the engine, let it warm up and turn the engine off.
- Engage the Parking brake.
- Place a suitable container / pan that holds at least 2.5 liters under the engine.
- Loosen the drain plug at the bottom of the engine (17mm Hex Screw). Do not drop the screw into the pan.
- Carefully drain warm oil and allow it to drain completely. **WARNING: OIL CAN BE VERY HOT!**
- Remove the oil filter. The oil filter is located under the cover on the right side of the engine.
- Loosen the 3 screws from the cover and remove the oil filter. Allow the oil to drain from the filter.
- Wipe away any spilled oil.
- Replace the gasket / O-Ring (under the cover) and insert the new filter with the new ring into the engine.
- Screw the oil filter cover back on. Tightening torque: 10Nm
- Screw the oil drain plug back into the engine. Tightening torque: 30 Nm.
- Unscrew and remove the oil dip stick – the oil filling point.
- Using a funnel, carefully pour about 2 liters of 10W-40 oil into the engine. Avoid overfilling the funnel.
- Put the dip stick on top of the threads (screw it in), pull the dip stick out and check the oil level.
- If the oil level is low, top up the oil.
- If the oil level reaches the upper mark on the dip stick, reinstall the dip stick.
- In general, you should use about 2.4 liters of oil when changing.
- Clean spilled oil, start the engine and check for oil leaks.
- After cca. 1 minute stop the engine, wait for about 10 seconds, unscrew the oil dip stick again and wipe it with a clean rag. Put the dip stick on top of the threads (screw it in), pull the dip stick out and check the oil level.
- The oil level should be between the upper and lower marks.
- If not, add the oil to the correct level by repeating the steps above.
- Once the oil level is correct, screw the dip stick back into the engine and wipe off any oil residues. Congratulations: you have successfully replaced your oil and oil filter!
- Dispose of the used oil ecologically - take your used oil and oil filter in for recycling.

#### CHANGE-KIT-02 includes:

- **1x Filter**, Part: 910146
- **1x O-Ring**, Part: 910315
- **1x Gasket**, Part: 911024
- **3x 1L MAXIMA ATV PREMIUM 10W40 4T Motor Oil**, Part: 33901
- **Instruction sheet**



OFFICIAL DISTRIBUTOR: